

HPE Release Sets for HPE Integrity rx2800 i2, i4 and i6 server series

HPE Release Sets for HPE Integrity rx2800 i2, i4 and i6 servers are supported firmware combinations for the server and some server components. Integrity rx2800 i2, i4 and i6 system firmware update is supported by the HPE firmware installation tool SUM (Smart Update Manager). Firmware update for some other servers or components may be supported via other tools. To find the appropriate installation tools for all Integrity Servers, see [HP Integrity and HP 9000 Servers – HP Firmware Update Options](#) (PDF 307 KB).

Use the links below to download firmware for the rx2800 i2, i4 and i6 server or the components listed, or visit [HPE Support and Drivers](#).

Note: SUM bundles are run from networked Windows or Linux client workstations and are used to update Integrity platforms running all supported Integrity operating systems including HP-UX. For example, to update an rx2800 i2 server running HP-UX 11i v3 from a Linux networked workstation, choose the SUM Linux bundle. For more information on SUM, please see the [User Guide](#).

HPE rx2800 i2 server Firmware Components	HPE rx2800 i2 version 28.00 - Jan 2017	HPE rx2800 i2 version 29.00 - Dec 2017	HPE rx2800 i2 version 29.00 - Mar 2018
HPE rx2800 i2 System Firmware for SUM (Includes binaries for SFW, iLO, FPGA, Power monitor)	For HP-UX 11i v3 (OE March 2010 or later), Windows server 2008 R2, OpenVMS 8.4 Same bundle applies to all rx2800 i2 servers: 28.00 (Windows based SUM bundle) 28.00 (Linux based SUM bundle)	For HP-UX 11i v3 (OE March 2010 or later), Windows server 2008 R2, OpenVMS 8.4 Same bundle applies to all rx2800 i2 servers: 29.00 (Windows based SUM bundle) 29.00 (Linux based SUM bundle)	For HP-UX 11i v3 (OE March 2010 or later), Windows server 2008 R2, OpenVMS 8.4 Same bundle applies to all rx2800 i2 servers: 29.00 (Windows based SUM bundle) 29.00 (Linux based SUM bundle)
HPE rx2800 i2 p410i embedded IO update bundle (Includes binary for SAS FW)	Onboard IO Update 6.42 HP-UX version 6.42 EFI version	Onboard IO Update 6.64 HP-UX version 6.64 EFI version	Onboard IO Update 6.64 HP-UX version 6.64 EFI version
HPE rx2800 i2 LOM (Lan on Motherboard)	4.3.02 EFI version	4.3.02 EFI version	4.3.02 EFI version

HPE rx2800/ rx2900 i4/i6 server Firmware Components	HPE rx2800 i4, rx2900 i4 version 47.00	HPE rx2800 i4, rx2900 i4 version 49.01	HPE rx2800 i4, rx2900 i4, rx2800 i6, rx2900 i6 version 50.00
HPE rx2800/ rx2900 i4/i6 System Firmware for SUM (Includes binaries for SFW, iLO, FPGA, Power monitor)	For HP-UX 11i v3 (OE Sept 2012 or later) 47.00 (Windows-based SUM bundle) 47.00 (Linux-based SUM bundle)	For HP-UX 11i v3 (OE Sept 2012 or later) 49.01 (Windows-based SUM bundle) 49.01 (Linux-based SUM bundle)	For HP-UX 11i v3 (OE Sept 2012 or later) 50.00 (Windows-based SUM bundle) 50.00 (Linux-based SUM bundle)
HPE rx2800/ rx2900 i4/i6 p410i embedded IO update bundle (Includes binary for SAS FW)	6.42 (EFI) 6.42 (HP-UX)	6.42(a) EFI 6.42 (HP-UX)	6.64 (HP-UX) 6.64 EFI version
HPE rx2800 /rx2900 i4/i6 LOM (Lan On Motherboard)	4.3.02 (HP-UX): part of 2014.10.27	4.3.02(a) (EFI) 4.3.02 (HP-UX): part of 2014.10.27	4.3.02(a) (EFI) 4.3.02 (HP-UX): part of 2014.10.27

--	--	--	--

Note: rx2800 i6 & rx2900 i6 servers require firmware version 49.01 or later.

rx2800 i2, rx2800/rx2900 i4, rx2900 i6 add-on IO FW and EFI drivers

The IO firmware bits are now also included in Firmware Flash bundles for SUM 5.3.0 or later and posted on the rx2800 i2, rx2800 i4, rx2900 i4, rx2800 i6 and rx2900 i6 server download pages.

The latest versions are:

For Intel cards and for Broadcom cards with a IEXGBE-DRV version lower than B.11.31.1303, use:

» HPE Firmware Flash Component for Intel and Broadcom adapters [2014.2.18](#)

For Intel cards and for Broadcom cards with a IEXGBE-DRV version B.11.31.1303 or greater, use:

» HPE Firmware Flash Component for Broadcom NIC HP-UX [2014.10.27](#)

» HPE Firmware Flash for Infiniband Adapters [2012.11.30](#)

» HPE Firmware Flash for Emulex Adapters [2015.05.21\(a\)](#)

» HPE Firmware Flash for Qlogic Adapters [2016.06.30](#)

» HPE Firmware Flash for Smart Array Adapters [2013.09.25](#)

Networking:

» PCIe 10 GbE SR/LR/CR (AM225A/AM232A/AM233A): EFI [5.2.60](#), ROM [6.2.28](#)

» PCIe 1000BT/BSX (2p AD337A, 2p AD338A, 4p AD339A): LAN EFI [4.3.02](#)

» PCIe 2-port 561T 10 GbE (B9F25A): [4.4.30](#), [5.0.20](#)

FCoE:

» PCIe 2-port CN1100E CNA (AT111A): EFI [4.9.416.12](#)

Smart Array:

» P411/256MB (AM311A) EFI version: [6.42](#)

» P812/1GB (AM312A) EFI version: [6.42](#)

FibreChannel

» PCIe 8Gb FC SR 1p/2p Qlogic (AH400A/AH401A): EFI [2.27](#) (not supported on i6 servers)

» PCIe 8Gb FC SR 1p/2p Emulex (AH402A/AH403A): [2.02x2](#), EFI [4.01.a5](#) (not supported on i6 servers)

» PCIe 1p/2p 16Gb FC Qlogic HBA (B9F23A/B9F24A):_EFI 6.37, ROM 8.01.80 (part of [2016.06.30](#))

Fibre Channel + Networking:

» PCIe 4GB FC and 1000BT/BSX (1-port AD221A or 2-port AD222A or AD393A): FC ROM: **2.82x4**, FC EFI: 4.01a5; LAN **4.3.02** (not supported on i6 servers) : part of [2015.05.21](#)

» PCIe 2-port 8GB FC and 2-port 1/10GB (AT094A): FC: [EFI 4.01.a5 \(FW 2.02x2, UBC 5.03a15\)](#) part of [2015.05.21](#) ; LAN: FW [4.9.416.12](#) (EFI: 49.00a11)

Infiniband

» HPE 4X QDR IB (AT083A): FW version 2.9.1000 – included in the Firmware Flash for Infiniband Adapters [2012.11.30](#)

For more information on SUM, please visit <http://www.hpe.com/info/sum-docs>